EZY-TURN [°] #196 HI TEMP / HI PRESSURE VALVE SEAT SEALANT & BODY FILLER

DESCRIPTION

EZY-TURN® #196 (JL Special 196) is a premium sealant formulated from a unique blend of high viscosity gas resistant synthetic and vegetable based oils for use in all valve types. Ideal sealant for service applications involving gases, distillates, dilute acids and steam. EZY-TURN **#196** contains special space age polymeric fibers and other sliding lubricants to enhance sealability in extreme applications. Although designed for expanding gate type valves, EZY-TURN #196 is used effectively on many other valve types.

- Nontoxic
- Vegetable & Synthetic Base Water resistant

Pumpable

- Nonhazardous Enhanced Solid Fillers · Multi-Purpose
 - Hydrocarbon Resistant
- Reduces Torque Seals, Lubricates

APPLICATIONS

Oilfield: EZY-TURN #196 has been formulated for use in production oilfield situations (Christmas trees, line valves) where a variety of service conditions may be required. This is a premium product and should be used where typical solid fillers mandated in the "peanut butter" type sealants do not work. The new space age polymeric fibers add greater performance for extreme services.

Industrial and Marine: EZY-TURN #196 is also recommended for gate valve applications requiring resistance to hydrocarbon or hydrocarbon/water mixtures.

SERVICE RECOMMENDATIONS

Petroleum Gases	Butane	
Petroleum Liquids	Propane	
Natural Gas	LPG	
Crude Distillates	Crude Oil	
Dilute Alkalies	Dilute Acids	
Aqueous Solutions	Salt Solutions	

XTEX

PRODUCT CHARACTERISTICS

Appearance	Gold to Amber Sticky Paste	
Penetration (ASTM D-217)	230 - 260	
Density (lb/gal) Typical	11.0	
Specific Gravity	1.32	
Dropping Point (ASTM D-2265)	None	
Oil Separation	5.0 max	
(FTMS 791.B M.321.2) (ASTM D-6184)		
Thickener	Inorganic	
Temperature Range	-0°F (-18°C) to	
	420°F (215°C)	
Biodegradibility (ASTM D-5864)	<50mg./3.0 lts.	

Note: Not for use with oxygen or strong oxidizers

PACKAGING

Part No.	Container Size	Container
95016	5 gal / 20 litre	Pail

LIMITED WARRANTY

Jet-Lube, Inc. makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube, Inc. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and

of any other obligation on the part of Jet-Lube, Inc. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube, Inc. shall not be liable for incidental or consequential damages.

Distributed By

Phone - 1 300 00 XTEX (9839) E-Mail - sales@xtex.com.au Web - www.xtex.com.au