# MP SILICONE GREASE ™ MOISTURE PROOFING, NONCONDUCTIVE LUBRICANT

#### **DESCRIPTION**

JET-LUBE® MP SILICONE GREASE™ is a premium silicone grease for use in a wide variety of applications. Ideal for lubricating and moisture-proofing marine, automotive and aircraft ignition systems, electrical assemblies, cable connections, battery terminals and spark plug connectors. It can also be used as a release agent and lubricant for both plastic and metal parts.

Thickener Fluid Type Color/Appearance

Dropping Point (ASTM D-566)
Specific Gravity

Density (Ib/gal) Typical

The low volatility and inert properties allow it to be used on a wide range of elastomers and plastics. It is not recommended for use on surfaces to be painted.

- · Will not carbonize at high temperatures
- NSF H-1 Registered
- Excellent for high temperature bearings, conveyor systems, and low-temp refrigeration systems.
- Water resistant
- Nontoxic/Safe
- Wide temperature range
- Translucent paste
- Highly resistant to oxidation and shear breakdown
- Dielectric strength: 500 volts/mil typical

» NSF H-1 Registered, #127362 «
» Meets USDA 1998 H-1 Guidelines «

### PRODUCT CHARACTERISTICS

Thickener Inorganic Fluid Type Silicone Color/Appearance Translucent to opaque gel/paste None Specific Gravity 1.01-1.06 Density (lb/gal), Typical 8.4-8.8 Flash Point (ASTM D-92), Typical >500°F (260°C) Autoignition Point (Calculated) 600°F (316°C) NLGI Grade, Standard ~2 Penetration 275 - 305Copper Strip Corrosion 1A (ASTM D-4048) <1.0% Oil Separation, Wt. %

(24 hrs. @ 100°C)
Temperature Range -70°F (-57°C) to 400°F (204°C)
Dielectric Breakdown Voltage 500 volts/mil

Dielectric Breakdown Voltage (ASTM D149), Typical

#### **PACKAGING**

Part No.	Container Size	Container
32460	148 ml / 225 gm	Tube
32450	14 oz. / 394 gm	Cartridge
32416	5 gal / 20 litre	Pail

### LIMITED WARRANTY

Jet-Lube, Inc. makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube, Inc. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube, Inc.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube, Inc. shall not be liable for incidental or consequential damages.

## **Distributed By**



Phone - 1 300 00 XTEX (9839) E-Mail - sales@xtex.com.au Web - www.xtex.com.au