

# EZY-TURN® #7

## BALL VALVE SEALANT



VALVE  
VALVE  
VALVE  
VALVE  
VALVE

### DESCRIPTION

**EZY-TURN® #7** ball valve sealant is formulated from premium food grade synthetic fluids for maximum hydrocarbon resistance over a broad temperature range. Pumpable and usable at temperatures as low as -30°F (-35°C). It also retains its firm consistency at temperatures as high as 400°F (204°C) when injected into the valve and oxygen contact is avoided. Fortified with inhibitors against H<sub>2</sub>S, rust and oxidation.

- Synthetic base
- Color: Blue
- H<sub>2</sub>S Inhibited
- Corrosion resistant
- Stops galling
- Biodegradable
- Water resistant
- Biodegradable
- Nontoxic
- Pumpable

### APPLICATIONS

**EZY-TURN #7** is an all purpose sealant for use in any application involving aliphatic hydrocarbon product streams.

**EZY-TURN #7** is resistant to water and aqueous services, but is not recommended for steam service. Ideal for use in ball valves where the temperature range of conventional vegetable oil sealants precludes their use. Particularly well suited for low temperature applications -30°F (-35°C) to 20°F (-7°C). Will not dissolve in aliphatic hydrocarbon services and prevents scoring and galling on precision valve surfaces.

**Note: Not for use with oxygen or strong oxidizers such as hydrogen peroxide or sulfuric acid.**

### SERVICE RECOMMENDATIONS

- Aliphatic Hydrocarbons
- Crude
- Natural Gas
- LPG
- Diesel
- Dilute Acids & Bases
- Water
- Aqueous Solutions

### TEMPERATURE RANGE

-30°F (-35°C) to 400°F (204°C)

### PRODUCT CHARACTERISTICS

Appearance	Blue
Penetration (ASTM D-217)	310 Typical
Density (lb/gal) Typical	9.15
Specific Gravity	1.1
Dropping Point (ASTM D-2265)	None
Oil Separation (ASTM D-6184) (FTMS 791.B M.321.2)	5.0 max
Thickener	Inorganic
Flash Point F°(C°) (ASTM D-92)	>450 (232)
pH Range	3 - 9

### PACKAGING

Part No.	Container Size	Container
94316	5 gal / 20 litre	Pail

### LIMITED WARRANTY

Jet-Lube, Inc. makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube, Inc. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube, Inc.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube, Inc. shall not be liable for incidental or consequential damages.

## Distributed By



Phone - 1 300 00 XTEX (9839)  
E-Mail - sales@xtex.com.au  
Web - www.xtex.com.au