



BULLSEYE™

WATER WELL & ENVIRONMENTAL COMPOUND

DESCRIPTION

BULLSEYE™ is a high-purity thread compound designed for sensitive water-well and other environmental drilling applications requiring the use of a petroleum hydrocarbon-free product. **BULLSEYE** is formulated from a synergistic blend of vegetable oil and nonmetallic, inorganic, EP, and anti-wear additives. **BULLSEYE** provides maximum protection against galling, seizing, and damage to threads while maintaining water well integrity.

BULLSEYE is an all-weather product and is completely brushable from 20°F (-7°C) to 400°F (204°C) while retaining its buttery texture at temperatures exceeding 400°F (204°C).

- Petroleum-Hydrocarbon free
- Water resistant
- Drilling mud resistant
- Biodegradable
- Corrosion inhibited
- Vegetable-based fluids
- Nontoxic
- Conforms to assembly bill 1953
- Contains no VOC's

APPLICATIONS

For water well and other environmental drilling applications. Not intended for monitor well drilling programs. For monitor wells and more sensitive or difficult conditions, use JET- LUBE WELL-GUARD®.

PRODUCT CHARACTERISTICS

Thickener	Silica
Fluid Type	Vegetable
Appearance	Grainy Yellow Paste
Dropping Point (ASTM D-2265)	None
Specific Gravity	1.11
Density (lb/gal) Typical	9.25
Oil Separation,	<2
Wt.% Loss @ 212°F (100°C) (FTMS 791.B M.321.2)	
Penetration (ASTM D-217)	290 - 315
Service Rating	20°F (-7°C) to 400°F (204°C)

Note: Not for use with oxygen or strong oxidizers.

Distributed By



1-300-00-XTEX (9839)
sales@xtex.com.au
xtex.com.au

LIMITED WARRANTY

For warranty information please go to www.jetlube.com/pdf/Jet-Lube_Warranty.pdf.