

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations Issue date: 15/03/2022 Revision date: 26/04/2023 Supersedes: 15/03/2022 Version: 2.0

SECTION 1: Product identifier

1.1. GHS Product identifier

Product form : Mixture

MOLY-MIST™ Aerosol Trade name

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

No additional information available

1.4. Details of manufacturer or importer

Whitmore Manufacturing LLC 930 Whitmore Drive Rockwall, Texas 75087 USA

T 1.972.771.1000

Regulatory@whitmores.com - www.jetlube.com

Distributor

XTEX ABN 40 121 722 236 20 Trevi Crescent

Tullamarine, VIC 3043

AUS

T 1300-00-XTEX(9839)

sales@xtex.com.au - xtex.com.au

1.5. Emergency phone number

For Chemical Emergency Call CHEMTREC 24hr/day 7days/week **Emergency number**

Within USA and Canada: 1.800.424.9300 Outside USA and Canada: +1.703.527.3887

(collect calls accepted)

Country	Organisation/Company	Address	Emergency number	Comment
Australia	NSW Poisons Information Centre The Children's Hospital at Westmead	Locked Bag 4001 NSW 2145	13 11 26	
Australia	Chemtrec - Australia	Sydney	Local (City) +61 2 9037 2994	
Australia	Chemtrec - Australia		Toll Free 1800 862 115	

SECTION 2: Hazard identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Aerosol, Category 1 H222;H229 Serious eye damage/eye irritation, Category 2A H319 Germ cell mutagenicity, Category 1B H340 Carcinogenicity, Category 1B H350 Specific target organ toxicity - Single exposure, Category 3, Narcosis H336

2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU)







Flame

Exclamation Health hazard

Signal word (GHS AU)

: Danger

26/04/2023 (Revision date) AU - en 1/10

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

acetone (38.9532 %); Methyl ethyl ketone (15.6 %); Solvent Naphtha, light aromatic Contains

(0.2679534%)

Hazard statements (GHS AU) H222 - Extremely flammable aerosol

H229 - Pressurised container: May burst if heated

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

H340 - May cause genetic defects

H350 - May cause cancer

Precautionary statements (GHS AU) P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 - Wash hands, forearms and face thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P308+P313 - IF exposed or concerned: Get medical advice/attention.

P312 - Call a POISON CENTER or doctor if you feel unwell. P337+P313 - If eye irritation persists: Get medical advice/attention.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P405 - Store locked up.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition and information on ingredients

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
acetone	67-64-1	38.9532	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Methyl ethyl ketone	78-93-3	15.6	Flam. Liq. 2, H225 Acute Tox. 5 (Oral), H303 Eye Irrit. 2A, H319 STOT SE 3, H336
Solvent Naphtha, light aromatic	64742-95-6	0.2679534	Flam. Liq. 2, H225 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
Other substances (not contributing to the classification of this product)	-	45.18	-

SECTION 4: First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general Call a poison center or a doctor if you feel unwell.

First-aid measures after inhalation Remove person to fresh air and keep comfortable for breathing. First-aid measures after skin contact

Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get

medical advice/attention.

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy First-aid measures after eye contact

to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion Call a poison center or a doctor if you feel unwell.

26/04/2023 (Revision date) AU - en 2/10

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

4.2. Symptoms caused by exposure

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Irritation.
Symptoms/effects after eye contact : Eye irritation.

4.3. Medical attention and special treatment

Other medical advice or treatment : Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Pressurised container: May burst if heated.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Exercise caution. Spill area may be slippery. No open flames, no sparks, and no smoking.

Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and materials for containment and cleaning up

Methods for cleaning up : Mechanically recover the product.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal

protective equipment.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this

product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked

up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

26/04/2023 (Revision date) AU - en 3/10

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

SECTION 8: Exposure controls and personal protection

8.1. Control parameters - exposure standards

acetone (67-64-1)		
Australia - Occupational Exposure Limits		
Local name	Acetone	
OES TWA [1]	1185 mg/m³	
OES TWA [2]	500 ppm	
OES STEL	2375 mg/m³	
OES STEL [ppm]	1000 ppm	
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)	
Methyl ethyl ketone (78-93-3)		
Australia - Occupational Exposure Limits		
Local name Methyl ethyl ketone (MEK; 2-Butanone)		
OES TWA [1]	445 mg/m³	
OES TWA [2]	150 ppm	
OES STEL	890 mg/m³	
OES STEL [ppm]	300 ppm	
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)	

8.2. Biological Monitoring

No additional information available

8.3. Engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

8.4. Individual protection measures, such as personal protective equipment (PPE)

Hand protection : Neoprene or nitrile rubber gloves

Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR), Neoprene rubber (HNBR)	2 (> 30 minutes)	0.3 mm - 0.6 mm		

Eye protection : Chemical goggles or safety glasses Skin and body protection : Wear suitable protective clothing Respiratory protection Wear appropriate mask

Environmental exposure controls Avoid release to the environment.

SECTION 9: Physical and chemical properties

Physical state Liquid Appearance Aerosols. Colour Black Odour Acetone odour Odour threshold No data available No data available рΗ pH solution No data available Relative evaporation rate (butylacetate=1) No data available

Melting point / Freezing point Melting point: Not applicable > 36 °C (Based on components)

Boiling point Flash point < 0 °C (Liquid portion) Auto-ignition temperature No data available Flammability No data available Vapour pressure No data available Relative density No data available Density No data available Solubility Insoluble in water.

26/04/2023 (Revision date) AU - en 4/10

Safety Data Sheet

STOT-repeated exposure

Aspiration hazard

according to the Work Health and Safety (WHS) Regulations

Partition coefficient n-octanol/water (Log Pow) : No data available

Explosive properties : Pressurised container: May burst if heated.

Explosive limits : No data available
Minimum ignition energy : No data available
Fat solubility : No data available
Gas group : Press. Gas (Liq.)

SECTION 10: Stability and reactivity

Reactivity : Extremely flammable aerosol. Pressurised container: May burst if heated.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : No dangerous reactions known under normal conditions of use.

Conditions to avoid : Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of

ignition.

Incompatible materials : No additional information available

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not

be produced.

SECTION 11: Toxicological information

Acute toxicity (oral) : Not classified Acute toxicity (dermal) : Not classified Acute toxicity (inhalation) : Not classified

acetone (67-64-1)	
LD50 oral rat	5800 mg/kg bodyweight Animal: rat, Animal sex: female
LD50 dermal rabbit	20000 mg/kg (Equivalent or similar to OECD 402, Rabbit, Male, Experimental value, Dermal)
LC50 Inhalation - Rat	76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4
LC50 Inhalation - Rat (Vapours)	76 mg/l Source: ECHA
Methyl ethyl ketone (78-93-3)	
LD50 oral rat	2193 mg/kg bodyweight (Equivalent or similar to OECD 423, Rat, Male / female, Readacross, Oral)
LD50 dermal rabbit	> 10 ml/kg (Equivalent or similar to OECD 402, 24 h, Rabbit, Male, Experimental value, Dermal)
LC50 Inhalation - Rat (Vapours)	34.5 mg/l/4h
Solvent Naphtha, light aromatic (64742-	95-6)
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: May cause genetic defects.
Carcinogenicity	: May cause cancer.
Reproductive toxicity	: Not classified
acetone (67-64-1)	
LOAEL (animal/female, F0/P)	11298 mg/kg bodyweight Animal: mouse, Animal sex: female
NOAEL (animal/male, F0/P)	900 mg/kg bodyweight Animal: rat, Animal sex: male, Remarks on results: other:Generation not specified (migrated information)
STOT-single exposure	: May cause drowsiness or dizziness.
acetone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.
Methyl ethyl ketone (78-93-3)	
STOT-single exposure	May cause drowsiness or dizziness.

: Not classified

: Not classified

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

MOLY-MIST™ Aerosol		
Vaporizer	Aerosol	
acetone (67-64-1)		
Animal studies and expert judgment for classification False		
Viscosity, kinematic	0.417 mm²/s	
Methyl ethyl ketone (78-93-3)		
Animal studies and expert judgment for classification	False	
Viscosity, kinematic	0.494 mm²/s	
Solvent Naphtha, light aromatic (64742-95-6)		
Animal studies and expert judgment for classification False		
Viscosity, kinematic	< 1 mm²/s Temp.: 'other:37.8°C' Parameter: 'kinematic viscosity (in mm²/s)'	

SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

12.1. Ecotoxicity

Toxic to aquatic life with long lasting effects.

Ecology - general Hazardous to the aquatic environment, short–term

: Not classified

Hazardous to the aquatic environment, long-term

: Toxic to aquatic life with long lasting effects

(chronic)

acetone (67-64-1)			
LC50 - Fish [1]	5540 mg/l (EU Method C.1, 96 h, Salmo gairdneri, Static system, Fresh water, Experimental value, Nominal concentration)		
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'		
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'		
BCF - Fish [1]	0.69 (Pisces)		
BCF - Other aquatic organisms [1]	3 (BCFWIN, Calculated value)		
Partition coefficient n-octanol/water (Log Pow)	-0.24 (Test data)		
Methyl ethyl ketone (78-93-3)			
LC50 - Fish [1]	2993 mg/l Test organisms (species): Pimephales promelas		
EC50 - Crustacea [1]	308 mg/l Test organisms (species): Daphnia magna		
ErC50 algae	1972 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)		
NOEC chronic algae	93 mg/l		
Partition coefficient n-octanol/water (Log Pow)	0.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 40 °C)		
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.53 (log Koc, Calculated value)		
Solvent Naphtha, light aromatic (64742-95-6)			
Partition coefficient n-octanol/water (Log Pow)	2.1 – 6		

12.2. Persistence and degradability

acetone (67-64-1)	
Not rapidly degradable	
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

acetone (67-64-1)		
Biochemical oxygen demand (BOD)	1.43 g O ₂ /g substance	
Chemical oxygen demand (COD)	1.92 g O₂/g substance	
ThOD	2.2 g O ₂ /g substance	
BOD (% of ThOD)	0.872 (20 day(s), Literature study)	
Methyl ethyl ketone (78-93-3)		
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.	
Biochemical oxygen demand (BOD)	2.03 g O ₂ /g substance	
Chemical oxygen demand (COD)	2.31 g O ₂ /g substance	
ThOD	2.44 g O ₂ /g substance	
Solvent Naphtha, light aromatic (64742-95-6)		
Not rapidly degradable		

12.3. Bioaccumulative potential

acetone (67-64-1)		
BCF - Fish [1]	0.69 (Pisces)	
BCF - Other aquatic organisms [1]	3 (BCFWIN, Calculated value)	
Partition coefficient n-octanol/water (Log Pow)	-0.24 (Test data)	
Bioaccumulative potential	Not bioaccumulative.	
Methyl ethyl ketone (78-93-3)		
Partition coefficient n-octanol/water (Log Pow)	0.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 40 °C)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.53 (log Koc, Calculated value)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
Solvent Naphtha, light aromatic (64742-95-6)		
Partition coefficient n-octanol/water (Log Pow)	2.1 – 6	

12.4. Mobility in soil

acetone (67-64-1)		
Surface tension	0.0237 N/m	
Ecology - soil	No (test) data on mobility of the substance available.	
Partition coefficient n-octanol/water (Log Pow)	-0.24 (Test data)	
Methyl ethyl ketone (78-93-3)		
Surface tension	0.024 N/m (20 °C)	
Ecology - soil	Highly mobile in soil. Slightly harmful to plants.	
Partition coefficient n-octanol/water (Log Pow)	0.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 40 °C)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.53 (log Koc, Calculated value)	
Solvent Naphtha, light aromatic (64742-95-6)		
Partition coefficient n-octanol/water (Log Pow)	2.1 – 6	

12.5. Other adverse effects

Ozone

: Not classified: No additional information available Other adverse effects

7/10 26/04/2023 (Revision date) AU - en

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

MOLY-MIST™ Aerosol		
Fluorinated greenhouse gases	False	
acetone (67-64-1)		
Fluorinated greenhouse gases False		
Methyl ethyl ketone (78-93-3)		
Fluorinated greenhouse gases False		
Solvent Naphtha, light aromatic (64742-95-6)		
Fluorinated greenhouse gases	False	

SECTION 13: Disposal considerations

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

400	IMPO	IATA
ADG	IMDG	IATA
14.1. UN number		
1950	1950	1950
14.2. UN Proper Shipping Name		
AEROSOLS	AEROSOLS	Aerosols, flammable
14.3. Transport hazard class(es)		
2.1	2.1	2.1
2	2	2
14.4. Packing group		
Not applicable	Not applicable	Not applicable
14.5. Environmental hazards		
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes

14.6. Special precautions for user

Specific storage requirement : No data available Shock sensitivity : No data available

14.7. Additional information

Other information : No supplementary information available

Transport by road and rail

UN-No. (ADG) : 1950

Special provision (ADG) : 63, 190, 277, 327, 344, 381

Limited quantities (ADG) : See SP 277
Excepted quantities (ADG) : E0
Packing instructions (ADG) : P207, LP200
Special packing provisions (ADG) : PP87, L2

Transport by sea

UN-No. (IMDG) : 1950

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959

Limited quantities (IMDG) : SP277
Excepted quantities (IMDG) : E0
Packing instructions (IMDG) : P207, LP200

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Special packing provisions (IMDG) : PP87, L2

EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES

EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)

Stowage category (IMDG) : None Stowage and handling (IMDG) : SW1, SW22 Segregation (IMDG) : SG69

Air transport

UN-No. (IATA) : 1950 PCA Excepted quantities (IATA) E0 PCA Limited quantities (IATA) Y203 PCA limited quantity max net quantity (IATA) 30kgG PCA packing instructions (IATA) 203 PCA max net quantity (IATA) 75kg CAO packing instructions (IATA) 203 CAO max net quantity (IATA) 150kg

Special provisions (IATA) : A145, A167, A802

ERG code (IATA) : 10L

14.8. Hazchem or Emergency Action Code

Hazchem Code : Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

No additional information available

15.2. International agreements

No additional information available

SECTION 16: Other information

Revision date : 26/04/2023

Classification		
Aerosol 1	H222;H229	
Eye Irrit. 2A	H319	
Muta. 1B	H340	
Carc. 1B	H350	
STOT SE 3	H336	

Full text of H-statements	
Acute Tox. 5 (Oral)	Acute toxicity (oral), Category 5
Aerosol 1	Aerosol, Category 1
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1B	Carcinogenicity, Category 1B
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 2	Flammable liquids, Category 2
Muta. 1B	Germ cell mutagenicity, Category 1B
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour
H303	May be harmful if swallowed
H304	May be fatal if swallowed and enters airways
H319	Causes serious eye irritation

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Full text of H-statements		
H336	May cause drowsiness or dizziness	
H340	May cause genetic defects	
H350	May cause cancer	

Safety Data Sheet (SDS), Australia

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.