



WHITE LITHIUM GREASE WITH PTFE

DESCRIPTION

WHITE LITHIUM GREASE with PTFE is a premium, all-purpose grease that provides superior performance and protection for metal and moving parts under any use.

WHITE LITHIUM GREASE with PTFE forms a long-lasting protective film to withstand heavy loads and high speeds, prevents rust and corrosion, eliminates squeaks and squeals and will not run or wash away.

WHITE LITHIUM GREASE with PTFE is excellent for all metal-to-metal lubrication and is the preferred lubricant for use in the plant, shop, home, auto and boat.

- Available in convenient aerosol package
- NSF Reg. #137549
- Clean, White Color
- Multi-Purpose
- Water Resistant
- Prevent Rust and Corrosion
- Very Adhesive
- Resists Heat and Oxidation

APPLICATIONS

GENERAL PURPOSE LUBRICANT

INDUSTRIAL - machinery, tools, overhead garage door channels, fan motors, slides, gears...

MARINE - cables, couplings, gears, hitches, winches...

AUTOMOTIVE - hinges, electric antennas, latches, springs, coils...

RESIDENTIAL - implements, door channels, slides, locks...

FOOD SERVICE - all areas where food contact cannot occur.

SERVICE RATING:
0°F (-18°C) to 370°F (190°C)

- NSF (H-2) Registered, Meets 1998 USDA (H-2) Guidelines For Use In Federally Inspected Meat and Poultry Plants in Noncontact Areas
- Authorized for use by Agriculture Canada

LIMITED WARRANTY

For warranty information please go to

www.jetlube.com/pdf/Jet-Lube_Warranty.pdf

PRODUCT CHARACTERISTICS

Thickener	Lith. 12-hydroxy
Fluid Type	Petroleum Oil
Color/Appearance	White
Dropping Point (ASTM D-566)	390°F (199°C)
Specific Gravity	0.95
Density (lbs/gal)	7.80
Additive Type	Organic E/P, A/W, R&O, PTFE
Flash Point (ASTM D-92)	
Bulk	>430°F (221°C)
Autoignition Point (calculated)	>500°F (260°C)
NLGI Grade	2
Penetration @ 77°F (ASTM D-217)	265 – 295
Copper Strip Corrosion (ASTM D-4048)	1A
4-Ball (ASTM D-2596)	
Weld Point, kgf	200
Load Wear Index	25
Wear Scar Diameter (ASTM D-2266)	0.7
Oxidation Resistance (ASTM D-942) PSI Drop, 100 hrs.	<5
Base Oil Viscosity (ASTM D-445) cSt @ 40°C	100 - 160

Distributed By



1-300-00-XTEX (9839)
sales@xtex.com.au
xtex.com.au

An ISO 9001 registered company