

Date Prepared: March 31, 2015

1. Product and Company Identification

Deacon Industries, Inc.
Bldg. #1, West Point Drive
P. O. Box 224
Washington, PA 15301 USA
Phone (724) 225-8008

24 Hour Emergency Response Contact:
CHEMTREC (USA and CANADA)
Phone: 800-424-9300 or 703-527-3887

Product Name: Deacon 4011
Product Type: Sealant Compound
Product Description: Brown Liquid
General Use : Thread Sealant / Gasket Dressing

2. Hazards Identification

GHS Classification : Carcinogenicity, 1A
Skin Irritation, 2
Eye Irritation, 2B

GHS Label Elements :
Signal Word : Warning

**Hazard Statements:**

H315 / 320 Causes Skin and Eye Irritation
H333 May be harmful if inhaled (respirable dust, see NOTE below)
H303 May be harmful if swallowed
H335 May cause respiratory irritation

Precautionary Statements :

P261 Avoid breathing dust/vapors
P262 Do not get in eyes, on skin, or on clothing
P285 In case of inadequate ventilation wear respiratory protection
P281 Use personal protective equipment as required
P301/P310 If Swallowed: Immediately call a Poison Center or Physician
P333/P313 If skin irritation or rash develops: Get medical attention.
P302/P352 If on skin: Wash with plenty of soap and water
P305/P351/P338 If in eyes : Rinse cautiously with water for several minutes.
Remove contact lenses if easy to do. Continue Rinsing.
P337/P313 If eye irritation persists: Get medical attention
P342/P311 If experiencing respiratory symptoms : Get medical attention.
P233 Keep container tightly closed
P210 Keep away from open flames. – No Smoking
P501 Dispose of observing all Federal, State and Local regulations.

NOTE: THIS PRODUCT IN ITS PURCHASED FORM DOES NOT PRESENT AN INHALATION HAZARD FROM FIBERS OR DUST, AS IT IS A LIQUID DUST IS NOT AIRBORN UNDER NORMAL HANDLING.

3. Composition / Information on Ingredients

Ingredients	CAS No.	% by weight
Crystalline Silica	None	<4
Modified Natural Resins	Proprietary	75-100

4. First Aid Measures

Ingestion: DO NOT INGEST. Oral toxicity not determined. Call a physician or get medical help immediately.

Inhalation: Remove to fresh air. If symptoms persist, seek medical attention.

Skin Contact: Wash with soap and water, consult physician if rash develops.

Eye Contact: Flush with water 15 minutes. If symptoms persist, seek medical attention.

5. Fire Fighting Measures

Recommended Extinguishing Agent:
Foam, Dry Chemical, Carbon Dioxide, Water Fog

Special Fire Fighting Procedures:
Self contained breathing apparatus and protective clothing should be worn in fighting fires involving chemicals. (Professionally Trained Personnel).

Hazardous Products Formed by Fire or Thermal Decomposition:
CO, CO₂, H₂S, SO₂, Smoke, Incomplete Combustion Products

Unusual Fire or Explosion Hazards:
Closed containers may rupture when exposed to extreme heat or fire conditions

Compressed Gases: None

Pressure at Room Temperature: Does not apply

6. Accidental Release Measures

Steps to be taken in cases of spill or leak:
Wear proper personal protective equipment. Remove any sources of ignition from the area and allow hot surfaces to cool. Return uncontaminated material to metal container and seal container tightly. Dispose of contaminated material or waste. Clean up with mineral spirits.

7. Handling and Storage

Storage: Cool, dry, storage below 90 degrees F. Store in closed containers. Refrigerate for best shelf life.

Handling: Avoid contact with skin and eyes. Do not breathe vapors. This product in its purchased form does not create an inhalation hazard from fibers or dust. If grinding or sanding or any other process is performed to this compound will cause airborne particles wear appropriate respirator to avoid breathing any dust or vapors. Wear appropriate safety gear as required in work area.

8. Exposure Controls / Personal Protection

Exposure Limits Ingredients	ACGIH (TLV)	OSHA (PEL)	OTHER
Crystalline Silica			
Cristobalite	0.05 mg/m3 (respirable)	0.025 mg/m3 (respirable)	
Tridymite	0.05 mg/m3 (respirable)		
Quartz	0.1 mg/m3 (respirable)	0.025 mg/m3 (respirable)	
Modified Natural Resins	10mg/m3	15mg/m3	
Personal Protective Equipment (PPE)			
Eyes:	Safety Glasses		
Skin:	Chemical resistant gloves such as impervious butyl or nitrile rubber gloves.		
Respiratory Protection:	NIOSH approved for organic vapors and dust.		
Other Protective Clothing or Equipment:	Coveralls or other protective clothing. Safety equipment as required in area.		
Work / Hygienic Practices:	Avoid contact with skin. Wash hands before eating.		
Engineering Controls :	Ventilation: Local exhaust if poorly ventilated area or in confined spaces. Ventilation should be provided during heat up to exhaust organic vapors resulting from vaporization of certain organic agents		

9. Chemical and Physical Properties

Appearance:	Brown Liquid	
Odor:	Pungent like	
pH:	7.2	
Solubility in Water:	NIL	
Specific Gravity:	1.0 (uncured) (H2O =1)	
Evaporation Rate:	Not Applicable	
Boiling Point:	Not Applicable	
Melting Point:	Not Applicable	
Vapor Pressure:	Not Applicable	
Vapor Density:	Not Established	
VOC Content:	None	
Flash Point:	more than 500 ⁰ F.	Method: Cleveland open

Flammable Limits:
LEL: Not Established
UEL: Not Established

10. Stability and Reactivity

Stability:	Stable
Hazardous Polymerization:	Will not occur
Hazardous Decomposition Or By-Products:	CO, CO2, H2S, SO2, Smoke, Incomplete Combustion Products
Incompatibility:	Strong Oxidizers and Strong Acids, Mineral Acids, Alkalies,

11. Toxicology Information

Primary Routes of Entry: Inhalation and contact.
Signs and Symptoms of Overexposure: **Inhalation:** respiratory irritation. **Eyes:** Redness and irritation.
Skin: Chemical dermatitis, redness and itching.

Existing Conditions Aggravated by Exposure: Pre-existing skin condition if prolonged exposure to skin. (Wear chemical resistant gloves) Respiratory disorders, asthma, chronic emphysema (if prolonged and continuous exposure to dust or vapors).
Dust exposure is not a hazard with this product under normal use. Product is in a liquid form. (Organic vapors , Wear recommended respirator if exceeding permissible exposure limit, see section 8)

Carcinogenicity
NTP: Crystalline Silica (respirable size) Known to be a Carcinogen

IARC: Crystalline Silica, Group 1 IARC

OSHA Regulated: NO

Toxicity :
No Information is available

Acute Health Hazards: **Skin:** Contact on bare skin can cause chemical dermatitis, redness, itching
Inhalation: Irritation

Chronic Health Hazards: **Inhalation:** Crystalline Silica, respirable size NTP Known Carcinogen.
Repeated exposure to solvent vapors above recommended exposure limits, can cause central nervous system effects, drowsiness, dizziness and headaches.
(Wear recommended respirator if exceeding permissible exposure limit, see section 8)

NOTE: THIS PRODUCT IN ITS PURCHASED FORM DOES NOT PRESENT AN INHALATION HAZARD FROM FIBERS OR DUST, AS IT IS A LIQUID. DUST IS NOT AIRBORN UNDER NORMAL HANDLING.

12. Ecological Information

None

13. Disposal Considerations

Recommended Methods of Disposal:
RCRA 40 CFR 261 Classification : This product as purchased does not fall under current US EPA RCRA definitions of Hazardous Waste.
Certain state regulations could affect whether a material is considered a hazardous waste upon disposal. It must also be noted that a material can become a hazardous waste if it is mixed with or comes in contact with a hazardous substance during use. Under RCRA it is the responsibility of user of a product to determine at the time of disposal, whether a material should be classified as a hazardous waste.

14. Transport Information

DOT (49 CFR 172): Not Regulated

IATA : Not Regulated

Liquid / Solid (per ASTM D 4359-90) : Material is a liquid

15. REGULATORY INFORMATION

CERCLA HAZARDOUS SUBSTANCES (40 CFR Part 302.4): This product is not reportable under 40 CFR Part 302.4.

SARA TITLE III SECTION 302 EXTREMELY HAZARDOUS SUBSTANCES (40 CFR Part 355): This product does not contain any SARA 302 Extremely Hazardous Substances.

SARA TITLE III SECTION 311/312 HAZARDOUS CATEGORIZATION (40 CFR Part 370): Certain ingredients of this product are regulated under Sara Title III Section 311/312, see section 3 of this MSDS.

SARA TITLE III SECTION 313 (40 CFR Part 372): None

U.S. INVENTORY (TSCA): Any chemical substances (as defined in 40 CFR Part 710.2), that are contained in, or used in the manufacture of this product, are reported in the EPA TSCA Inventory. (As required per 40 CFR 710.3)

CALIFORNIA PROPOSITION 65: Crystalline Silica

CANADA WHMIS: Ingredient Disclosure List: Crystalline Silica, quartz -- Crystalline Silica, Tridymite -- Crystalline Silica, Cristobalite

WHMIS Classification : Crystalline Silica, quartz: D2A

EUROPEAN UNION : Crystalline Silica: CLP Carc.1A

OZONE DEPLETERS: * This product is not manufactured with or contains any Class I or Class II Ozone Depleting Chemicals. (ODC's)

NOTE: THIS PRODUCT IN ITS PURCHASED FORM DOES NOT PRESENT AN INHALATION HAZARD FROM FIBERS OR DUST AS IT IS A LIQUID. DUST IS NOT AIRBORNE UNDER NORMAL HANDLING.

16. OTHER INFORMATION

The information contained in this MSDS sheet is based upon data supplied by our suppliers and data determined by us in our facilities at the time these products were formulated. We have reviewed any information that we received from sources outside our company. We believe that information to be correct but cannot guarantee its accuracy or completeness. Health and safety data in this sheet may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. If after reviewing this MSDS you have determined that this product poses unusual risks to you, your plant, or your plant personnel, or if you cannot comply fully with all safety recommendations, do not use this product. This product is intended for a temporary repair. The responsibility for whether or not the product is suitable for use rest solely with the purchaser. We recommend that the product be tested prior to use. Your use of this information is beyond our control, therefore, the information is provided without warranty expressed or implied. We accept no liability beyond the purchase price of the material.

Estimated HMIS® Code:

Health Hazard:	*1	* See section 11 for chronic effects.
Flammability Hazard:	1	
Physical Hazard:	0	

Personal Protection: NPCA recommends that PPE codes be determined by the employer, who is familiar with the actual conditions under which chemicals in the facility are used.

Procedural Warning:

Attn: Technician

(For Industrial use Only)

Avoid contact with skin and eyes. See section 8 of SDS for personal protective equipment.

Ventilation may be needed during heating/curing stage to exhaust organic vapors resulting from vaporization of certain organic agents. Always avoid direct contact with smoke and vapors being emitted from the compound during the heating/curing process. These vapors may be irritating to the skin, eyes and respiratory system. It is quite common that the application temperature will exceed the uncured compound flash point. Be aware of the possibility of a flash and take necessary precautions.

Read product technical data and safety information before using product.

PREPARATION INFORMATION

Prepared By:	Safety Department
Company:	Deacon Industries, Inc.
Revision Date:	03-31-15 Revision: E