

SAFETY DATA SHEET

Issuing Date 13-Jul-2012

Revision Date 02-Jun-2017

Revision Number 2

The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

Product identifier

Product Name C-PLATE™

Product Code(s) 61741

Other means of identification

Extended Description Aerosols

UN Number UN1950

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Lubricants, Greases and Release Products

Uses advised against No information available

Details of manufacturer or importer

Supplier Identification Address
XTEX
XTEX Ltd
ABN 40 121 722 236
7 Arnold Street
Cheltenham, VIC 3192

Telephone TEL: 1300-00-XTEX(9839)

E-mail sales@xtex.com.au

For further information, please contact

Responsible Persons Product Safety Department

Emergency telephone number

Emergency Telephone Number CHEMTREC: +1-703-527-3887 (INTERNATIONAL) Information Center, Australia: 13 11 26
Information Center, New Zealand: 0800 764 766

GHS Classification

Aerosols	Category 1
Gases Under Pressure	Compressed Gas
Acute toxicity - Dermal	Category 4 - (H312)
Acute toxicity - Inhalation (Vapors)	Category 4 - (H332)
Acute toxicity - Inhalation (Dusts/Mists)	Category 4 - (H332)
Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2A - (H319)
Germ cell mutagenicity	Category 1B - (H340)
Carcinogenicity	Category 1A - (H350)
Specific target organ toxicity (single exposure)	Category 3 - (H336)

Label elements

Flame
Exclamation mark
Health hazard

Signal word

Danger

Hazard statements

H222 - Extremely flammable aerosol
H280 - Contains gas under pressure; may explode if heated
H312 - Harmful in contact with skin
H332 - Harmful if inhaled
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H340 - May cause genetic defects
H350 - May cause cancer
H336 - May cause drowsiness or dizziness

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Avoid breathing dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area
Wash face, hands and any exposed skin thoroughly after handling
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
Pressurized container: Do not pierce or burn, even after use
Do not spray on an open flame or other ignition source

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
Specific treatment (see supplemental first aid instructions on this label)
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention
IF ON SKIN: Wash with plenty of soap and water

Call a POISON CENTER or doctor/physician if you feel unwell
If skin irritation occurs: Get medical advice/attention
Take off contaminated clothing and wash before reuse
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Precautionary Statements - Storage

Store locked up
Store in a well-ventilated place. Keep container tightly closed
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards

May be harmful if swallowed
Very toxic to aquatic life with long lasting effects

General Hazards No information available.

Substance

Not applicable.

Mixture

Chemical name	CAS-No	Percent
Petroleum gases	68476-85-7	10-30
Acetone	67-64-1	10-30
Xylenes (o-, m-, p- isomers)	1330-20-7	10-30
Methyl ethyl ketone	78-93-3	10-30
Copper (flake)	7440-50-8	1-5
Non-hazardous ingredients	Proprietary	Balance

First aid measures

General advice Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention.

Emergency telephone number Poisons Information Center, Australia: 13 11 26
Poisons Information Center, New Zealand: 0800 764 766

Inhalation Remove to fresh air. IF exposed or concerned: Get medical advice/attention. Get medical attention immediately if symptoms occur. If symptoms persist, call a physician. If breathing has stopped, give artificial respiration. Get medical attention immediately.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.

Skin contact Wash off immediately with soap and plenty of water for at least 15 minutes. If symptoms persist, call a physician.

Ingestion Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Get medical attention.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid breathing vapors or mists. Use personal protective equipment as required. See section 8 for more information.

Most important symptoms and effects, both acute and delayed

Symptoms Burning sensation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Coughing and/ or wheezing. Difficulty in breathing.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

Suitable Extinguishing Media

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO₂). Water spray.

Unsuitable extinguishing media DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

Specific hazards arising from the chemical

Specific hazards arising from the chemical

Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated.

Hazardous Combustion Products Carbon oxides

Special protective actions for fire-fighters

Special protective equipment for fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. Avoid breathing vapors or mists.

Other Information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Flood with water to complete polymerization and scrape off floor.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

Precautions to prevent secondary hazards

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

Precautions for safe handling

Advice on safe handling Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use spark-proof tools and explosion-proof equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid breathing vapors or mists. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. In case of insufficient ventilation, wear suitable respiratory equipment.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children.

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents.

Control parameters

Exposure Limits

Chemical name	Australia
Petroleum gases - 68476-85-7	1000 ppm 1800 mg/m ³
Acetone - 67-64-1	500 ppm 1185 mg/m ³ 1000 ppm STEL 2375 mg/m ³ STEL
Xylenes (o-, m-, p- isomers) - 1330-20-7	80 ppm 350 mg/m ³ 150 ppm STEL 655 mg/m ³ STEL
Methyl ethyl ketone - 78-93-3	150 ppm 445 mg/m ³ 300 ppm STEL 890 mg/m ³ STEL
Copper (flake) - 7440-50-8	1 mg/m ³ 0.2 mg/m ³

Legend See section 16 for terms and abbreviations.

Chemical name	Australia	ACGIH - American Conference of Governmental Industrial Hygienists
Acetone - 67-64-1	-	25 mg/L
Xylenes (o-, m-, p- isomers) - 1330-20-7	-	1.5 g/g creatinine
Methyl ethyl ketone - 78-93-3	-	2 mg/L

Appropriate engineering controls

Engineering controls Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.
Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.

Hand protection Impervious gloves. Wear suitable gloves.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Environmental exposure controls No information available.

Physical and Chemical Properties

Physical state	Aerosol
Appearance	Copper
Odor	Solvent
Color	No information available
Odor Threshold	Not applicable

<u>Property</u>	<u>Values</u>	<u>Remarks Method</u>
pH	7	
Melting / freezing point	-95 °C	None known
Boiling point / boiling range	-18 to 162 °C	None known
Flash Point	> -20 °C	None known
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		None known
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Relative density	0.76	
Water Solubility	Insoluble	
Solubility(ies)	No data available	

Partition coefficient: n-octanol/water Not applicable

None known

Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known

Other Information

Softening Point	No information available
Molecular Weight	No information available
VOC Content (%) <=606	No information available
Liquid Density	No information available
Bulk Density	No information available
Particle Size	No information available
Particle Size Distribution	No information available

Reactivity.

Reactivity No information available.

Chemical stability.

Stability Stable under normal conditions.

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge Yes.

Possibility of Hazardous Reactions

Possibility of hazardous reactions None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur

Conditions to avoid

Conditions to avoid Heat, flames and sparks. Excessive heat.

Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents.

Hazardous Decomposition Products

Hazardous Decomposition Products Carbon oxides.

Acute Toxicity

Information on likely routes of exposure

Product Information

Inhalation

Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. May cause drowsiness or dizziness. Harmful by inhalation. (based on components).

Eye contact

Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). Irritating to eyes.

Skin contact

Specific test data for the substance or mixture is not available. Harmful in contact with skin. Causes skin irritation. (based on components).

Ingestion

Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms

Redness. May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Coughing and/ or wheezing.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	3,559.00 mg/kg
ATEmix (dermal)	1,803.00 mg/kg
ATEmix (inhalation-gas)	4,500.00 ppm
ATEmix (inhalation-vapor)	17.00 mg/L
ATEmix (inhalation-dust/mist)	3.19 mg/L

Unknown acute toxicity 81.3 % of the mixture consists of ingredient(s) of unknown toxicity

- 40.8 % of the mixture consists of ingredient(s) of unknown acute oral toxicity
- 62.6 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity
- 81.3 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)
- 62.6 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)
- 59.5 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone	= 5800 mg/kg (Rat)	1700mg/kg (rabbit)	18892 mg/m ³
Xylenes (o-, m-, p- isomers)	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit) > 1700 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h = 5000 ppm (Rat) 4 h
Methyl ethyl ketone	= 2737 mg/kg (Rat)	= 6480 mg/kg (Rabbit)	23500 mg/m ³

Legend

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

Classification based on data available for ingredients. Irritating to skin.

Serious eye damage/eye irritation	Classification based on data available for ingredients. Irritating to eyes.
Respiratory or skin sensitization	No information available.
Germ cell mutagenicity	Classification based on data available for ingredients. Contains a known or suspected mutagen.
Carcinogenicity	Classification based on data available for ingredients. Contains a known or suspected carcinogen.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	Australia
Petroleum gases	Carc. 1B

Reproductive toxicity	No information available.
STOT - single exposure	May cause drowsiness or dizziness.
STOT - repeated exposure	No information available.
Aspiration hazard	No information available.

Ecotoxicity

Ecotoxicity	Very toxic to aquatic life with long lasting effects.
Unknown aquatic toxicity	36.7 % of the mixture consists of component(s) of unknown hazards to the aquatic environment.

Chemical name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Acetone	-	LC50 96 h: 4.74 - 6.33 mL/L (Oncorhynchus mykiss) LC50 96 h: 6210 - 8120 mg/L static (Pimephales promelas) LC50 96 h: = 8300 mg/L (Lepomis macrochirus)	EC50 = 14500 mg/L 15 min	EC50 48 h: 10294 - 17704 mg/L Static (Daphnia magna) EC50 48 h: 12600 - 12700 mg/L (Daphnia magna)

Xylenes (o-, m-, p-isomers)	EC50 72 h: = 11 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: = 13.4 mg/L flow-through (Pimephales promelas) LC50 96 h: 2.661 - 4.093 mg/L static (Oncorhynchus mykiss) LC50 96 h: 13.5 - 17.3 mg/L (Oncorhynchus mykiss) LC50 96 h: 13.1 - 16.5 mg/L flow-through (Lepomis macrochirus) LC50 96 h: = 19 mg/L (Lepomis macrochirus) LC50 96 h: 7.711 - 9.591 mg/L static (Lepomis macrochirus) LC50 96 h: 23.53 - 29.97 mg/L static (Pimephales promelas) LC50 96 h: = 780 mg/L semi-static (Cyprinus carpio) LC50 96 h: > 780 mg/L (Cyprinus carpio) LC50 96 h: 30.26 - 40.75 mg/L static (Poecilia reticulata)	EC50 = 0.0084 mg/L 24 h	EC50 48 h: = 3.82 mg/L (water flea) LC50 48 h: = 0.6 mg/L (Gammarus lacustris)
Methyl ethyl ketone	-	LC50 96 h: 3130-3320 mg/L flow-through (Pimephales promelas)	EC50 = 3403 mg/L 30 min EC50 = 3426 mg/L 5 min	EC50 48 h: 4025 - 6440 mg/L Static (Daphnia magna) EC50 48 h: = 5091 mg/L (Daphnia magna) EC50 48 h: > 520 mg/L (Daphnia magna)
Copper (flake)	96h EC50: 0.031 - 0.054 mg/L (Pseudokirchneriella)	96h LC50: 0.0068 - 0.0156 mg/L (Pimephales promelas) 96h LC50: =	-	48h EC50: = 0.03 mg/L

	subcapitata) 72h EC50: 0.0426 - 0.0535 mg/L (Pseudokirchneriella subcapitata)	1.25 mg/L (Lepomis macrochirus) 96h LC50: = 0.052 mg/L (Oncorhynchus mykiss) 96h LC50: = 0.2 mg/L (Pimephales promelas) 96h LC50: < 0.3 mg/L (Pimephales promelas) 96h LC50: = 0.112 mg/L (Poecilia reticulata) 96h LC50: = 0.3 mg/L (Cyprinus carpio) 96h		
--	-------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--	--

	LC50: = 0.8 mg/L (Cyprinus carpio)
--	---------------------------------------

Persistence and degradability

Persistence and Degradability No information available.

Bioaccumulative potential

Bioaccumulation

Component Information

Mobility

Mobility in soil No information available.

Mobility No information available.

Other adverse effects

Other adverse effects No information available.

Waste treatment methods

Waste from residues/unused products

Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Do not reuse empty containers.

ADG

UN Number	UN1950
Proper shipping name	Aerosols
Hazard Class	2

IATA

UN-No.	UN1950
Proper Shipping Name	Aerosols, flammable (Mixture)
Hazard Class	2.1
Packing Group	None
ERG Code	10L
Description	UN1950, Aerosols, flammable, 2.1, Mixture

IMDG/IMO

UN-No.	UN1950
Proper Shipping Name	Aerosols (Mixture)
Hazard Class	2.1
Packing Group	None
EmS-No.	F-D, S-U
Description	UN1950, Aerosols, 2.1, Mixture, FP -20C

Transport in bulk according to Annex II of MARPOL and the IBC Code

No information available

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Australia

See section 8 for national exposure control parameters

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

The below table provides the relevant information for classification of this product according to the regulation. This information should be used to appropriately determine if a classification is relevant to the overall product

Chemical name	Percent	Poison Schedule Number	Standard for the Uniform Scheduling of Drugs and Poisons(SUSDP)
Acetone 67-64-1	10-30	5	Schedule 5 (except in preparations containing <=25% of designated solvents)
Xylenes (o-, m-, p- isomers) 1330-20-7	10-30	6	Schedule 6 (except its derivatives;except in preparations containing <=50% of Xylene or Xylene and Toluene)
Methyl ethyl ketone 78-93-3	10-30	5	Schedule 5 (except in preparations containing <=25% of designated solvents)
Copper (flake) 7440-50-8	1-5	4 5 6	Schedule 4 (for human use except when separately specified in these Schedules;in preparations for human internal use containing <=5 mg of Copper per recommended daily dose;or in other preparations containing <=5% of Copper compounds)

Major hazard (accident/incident planning) regulation

Verify that license requirements are met

Named hazardous chemicals

Chemical name	Threshold quantity (T)
Petroleum gases - 68476-85-7	200 tonne TQ

National pollutant inventory

Subject to reporting requirement

Chemical name	National pollutant inventory
Acetone - 67-64-1	10 tonne/yr Threshold category 1 20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total
Xylenes (o-, m-, p- isomers) - 1330-20-7	10 tonne/yr Threshold category 1 including individual or mixed isomers 20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total
Methyl ethyl ketone - 78-93-3	10 tonne/yr Threshold category 1 20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total

Copper (flake) - 7440-50-8	10 tonne/yr Threshold category 1 2000 tonne/yr Threshold category 2b 60000 MWH Threshold category 2b 20 MW Threshold category 2b
----------------------------	----------------------------------------------------------------------------------------------------------------------------------

International Inventories

TSCA	Contact supplier for inventory compliance status.
DSL/NDSL	Complies.
EINECS/ELINCS	Complies.
ENCS	Complies.
KECL	Complies.
PICCS	Complies.
AICS	Complies.

Legend

- TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory
- DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List
- EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
- ENCS** - Japan Existing and New Chemical Substances
- KECL** - Korean Existing and Evaluated Chemical Substances
- PICCS** - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

International Regulations

Ozone-depleting substances (ODS) Not applicable

Persistent Organic Pollutants Not applicable

Export Notification requirements Not applicable

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Issuing Date 13-Jul-2012

Revision Date 02-Jun-2017

Revision Note Initial Release

Key or legend to abbreviations and acronyms used in the safety data sheet

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	-	Skin designation
C	Carcinogen		

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet