



# EZY-TURN® #3 ARCTIC

## GATE & PLUG VALVE SEALANT/LUBRICANT

### DESCRIPTION

EZY-TURN® #3 ARCTIC Gate and Plug Valve Sealant is specifically designed for use where light hydrocarbon liquids and gases are present, making it the sealant of choice for pipeline and compressor station usage. Pumpable to temperatures as low as -70°F (-57°C) with the appropriate pump.

Our proprietary blend of oils and solid lubricants, means EZY-TURN #3 ARCTIC lubricates and is resistant to all aliphatic hydrocarbons. Lowers torque necessary for smooth valve operation and protects internal plug surfaces from scoring and galling.

- Proprietary Oil Base
- Nontoxic
- Color: Grey/Black
- H<sub>2</sub>S Resistant
- Reduces Torque
- Stops Leaks
- Prevents Corrosion
- Biodegradable
- Stops Scoring, Galling
- Pumpable
- Nonhazardous

### APPLICATIONS

EZY-TURN #3 ARCTIC Gate and Plug Valve Sealant is ideal for any plug valve application requiring aliphatic liquid and gas resistance. Ideal for pipeline and compressor station operation. Excellent for use in heavy H<sub>2</sub>S, saline or salt water service.

**Recommended Cleanup:** Although conventional solvents like methanol, ethanol, IPA, chlorinated solvent, aromatic solvents, acetone and other ketones can be utilized, JET-LUBE® recommends its EZY-OPEN™ or other safe oxygenated solvents. EZY-OPEN is a nontoxic, nonflammable, biodegradable lubricant and cleanser specifically designed for valve cleaning applications. It contains no components listed as federal hazardous wastes.

**NOTE: Not for use with oxygen or strong oxidizers.**

### SERVICE RECOMMENDATIONS

- Aliphatic Hydrocarbons
- Butane
- Natural Gas
- LPG
- Hot Gases
- Propane
- Fuel Oil
- H<sub>2</sub>S, Saline, Salt Water

### TEMPERATURE RANGE

-70°F (-57°C) to 500°F (260°C)

### PRODUCT CHARACTERISTICS

Appearance	Grey/Black Paste
Cone Penetration @ 77°F (As manufactured, 300 strokes)	290 - 335
Density (lb/gal) Typical	8.80
Specific Gravity, Typical	1.06
Dropping Point (ASTM D-2265)	None
Oil Separation (FTMS 791.B M.321.2) (ASTM D-6184)	3.0 max
Thickener	Inorganic
Flash Point °F (°C) (ASTM D-92)	>500°F (260°C)
Temperature Range	-70°F (-57°C) to 500°F (260°C)

### PACKAGING

Part No.	Container Size	Container
93116	5 gal / 20 litre	Pail

### LIMITED WARRANTY

Jet-Lube, Inc. makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube, Inc. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube, Inc.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube, Inc. shall not be liable for incidental or consequential damages.

**Distributed By**



Phone - 1 300 00 XTEX (9839)  
E-Mail - sales@xtex.com.au  
Web - www.xtex.com.au

VALVE

VALVE

VALVE

VALVE

VALVE