

JET-LUBE[®] JACKING SYSTEM GREASE[™] ECF[™]

OSPAR Commission - HOCNF

Classification - "Yellow" Rating for Norway

- "E" for the United Kingdom & The Netherlands



DESCRIPTION

JET-LUBE[®] JACKING SYSTEM GREASE[™] ECF[™] is safe to use in offshore applications since it is metal free and is formulated to conform to the strict North Sea Environmental Guidelines. It utilizes a water-resistant, complex thickener that is enhanced to improve adhesion and provide greater protection against water washoff, wear, and corrosion. JET-LUBE JACKING SYSTEM GREASE ECF contains specially selected solid natural boundary lubricants to provide outstanding galling resistance and lubrication properties. The solid boundary and organic EP additives synergistically combine to produce a superior lubricating film with high-load and low-wear characteristics.

APPLICATIONS

JET-LUBE JACKING SYSTEM GREASE ECF is designed to lubricate a wide array of heavily loaded gear applications. It can also be used on slides, jacking systems, cantilever type rigs and assemblies, nuts, bolts, and a wide range of other applications - making JET-LUBE JACKING SYSTEM GREASE ECF a nearly universal product.

- Excellent Environmental Properties
- High Load Resistant
- Water Resistant
- Corrosion Resistant
- Nonmetallic
- Safe for Offshore Personnel
- Biodegradable, non-bioaccumulative
- Outstanding Film Strength
- Easy to Apply

This product is formulated to contain no detectable, leachable, volatile organics by EPA Test Method 1311-TCLP number SW846 8260B as determined by independent, 3rd party testing. Testing results are available upon request.

PRODUCT CHARACTERISTICS

Appearance	Beige Tacky Grease
Fluid Type	Synthetic & Vegetable
Thickener	Complex
Specific Gravity	1.26
Density (lbs/gal)	10.55
Cone Penetration	300 - 330
@ 77°F (ASTM D-217)	
Dropping Point	>200°F (93°C), typical
(ASTM D-2265)	
4-Ball (ASTM D-2596)	≥ 800
(7845) Weld Point, kgf (N)	
Gas Evolution	None,
typical Oil Separation	<1%, typical
Water Leaching	
2 hrs. @ 150°F	<5%, typical
Service Rating	-4°F (-20°C) to
	300°F (149°C)
EPA 1311-TCLP	Non-detected

PACKAGING

Part No.	Container Size	Container
25816	5 gal / 20 litre	Pail

LIMITED WARRANTY

Jet-Lube, Inc. makes the Limited Express Warranty that at the date of delivery this product shall be free from defects in Jet-Lube, Inc. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube, Inc.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube, Inc. shall not be liable for incidental or consequential damages.

Distributed By



Phone - 1 300 00 XTEX (9839)
E-Mail - sales@xtex.com.au
Web - www.xtex.com.au