# JET-LUBE® NO. 33

# JET-LUBE.

### **AUTOMOTIVE & INDUSTRIAL SILICONE GREASE**

#### **DESCRIPTION**

JET-LUBE® NO. 33 is specifically formulated to meet the automotive specifications for aftermarket rebuilders of water pumps, alternators, ignition systems, and all low-friction bearing applications. JET-LUBE NO. 33 is well suited for rubber parts, "O" ring materials, gaskets, and low-friction plastic bearings. Its low volatility and low temperature properties allow the product consistency to remain constant over a wide temperature range. JET-LUBE NO. 33 is especially effective in bearing applications where start up in extreme low temperatures is necessary.

- Resistant to moisture and corrosive environments
- Nontoxic/Safe
- Wide temperature range
- Chemical resistant
- Highly resistant to oxidation and shear breakdown
- Compatible with many plastics
- NLGI Grade 2
- Chemical resistant
- Conforms to CID A-A-59173, Type 2 (formerly MIL-G-46886B)
- Conforms to former MIL Spec G-4343 for pneumatic systems, now SAE-AMS-G-4343

#### Additional uses for JET-LUBE NO. 33 include:

- Freezer cart casters
- Utility disconnect switches and contacts
- Windshield wiper motors and gears
- Spiral freezer bearings
- Freezer door hinges

#### PRODUCT CHARACTERISTICS

Thickener	Lithium
Fluid Type	Silicone
Color/Appearance	Light Pink
Dropping Point (ASTM D-566)	392°F (200°C)
Specific Gravity	1.0
Density (lb/gal), Typical	8.3
Flash Point (ASTM D-92), Typical	560°F (293°C)
Autoignition Point (Calculated)	>600°F (316°C)
NLGI Grade, Standard	2
Approx. Safe DN Limit	350,000
Penetration	260 - 300
Copper Strip Corrosion	1A
(ASTM D-4048)	
Oil Separation, Wt. %	<1.0%
(24 hrs. @ 100°C) (ASTM D-6184)	
Service Rating	-70°F (-57°C) to

#### **PACKAGING**

Part No. 73860	Container Size 148 ml / 225 gm	Container Tube
73850	14 oz / 400 gm	Cartridge
73816	5 gal / 20 litre	Pail

400°F (204°C)

#### LIMITED WARRANTY

Jet-Lube, Inc. makes the Limited Express Warranty that at the date of delivery this product shall be free from defects in Jet-Lube, Inc. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube, Inc.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube, Inc. shall not be liable for incidental or consequential damages.

## **Distributed By**



Phone - 1 300 00 XTEX (9839) E-Mail - sales@xtex.com.au Web - www.xtex.com.au