

# MARINE WIRE ROPE AND HAWSER GREASE™



MARINE MARINE MARINE MARINE MARINE

## DESCRIPTION

**MARINE WIRE ROPE & HAWSER GREASE™** is an economical high-performance lubricant for wire rope, hawser, and related applications requiring a water resistant, tenacious product that resists the effects of fresh and salt water spray, oxidation, humidity, heat, and other adverse conditions common to marine and heavy industrial applications.

**MARINE WIRE ROPE & HAWSER GREASE** maintains and extends the life and performance of wire rope by providing a nondrying film on the outside of the wire rope. This film protects wire rope from corrosion while lubricating the inner strands, drums, and sheaves.

- White/Beige Color
- High Temperature
- Anti-Corrosive
- Protects
- NLGI Grade 2
- Nonstaining
- Water Resistant
- Lubricates
- Nondrying

## APPLICATIONS

Recommended for all marine and industrial wire rope, hawser and related activities such as shipyard gantry cranes, mast hoisting cables, loading cranes, offshore rig anchor cables, crane and drag lines, elevator hoist lines, or any wire rope cable that operates in harsh conditions.

## PRODUCT CHARACTERISTICS

|  |                                    |
|--|------------------------------------|
| Thickener                              | Lithium                            |
| Fluid Type                             | Petroleum Oil                      |
| Color/Appearance                       | White/Beige, Sticky Grease         |
| Dropping Point (ASTM D-2265)           | 390°F (199°C)                      |
| Specific Gravity                       | 0.95                               |
| Density (lb/gal)                       | 8.1                                |
| Flash Point (ASTM D-92)                | >430°F (221°C)                     |
| Additives                              | Boundary Lubricants, Polymers, R&O |
| Cone Penetration (ASTM D-217)          | 265 - 295                          |
| Copper Strip Corrosion (ASTM D-4048)   | 1B                                 |
| 4 Ball Weld Point                      | 315 Min.                           |
| Base Oil Viscosity                     | ISO 220, Typical                   |
| Oil Separation (Fed. Std. 791 M 321.2) | 5% Max.                            |
| Volatile Matter                        | Less than 2.0%                     |
| Timken OK Load                         | 55 lbs.                            |

## PACKAGING

| Part No. | Container Size   | Container |
|----------|------------------|-----------|
| 34516    | 5 gal / 20 litre | Pail      |

## SPECIFICATIONS

Meets or exceeds requirements of U. S. Military specification MIL-G-18458B (SH)

## TEMPERATURE RANGE

0°F (-18°C) to 325°F (163°C)

## LIMITED WARRANTY

Jet-Lube, Inc. makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube, Inc. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube, Inc.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube, Inc. shall not be liable for incidental or consequential damages.

## Distributed By



Phone - 1 300 00 XTEX (9839)  
 E-Mail - sales@xtex.com.au  
 Web - www.xtex.com.au